



Telequip®

Count On Us

Telequip® introduces the

CoinXpress™

*The complete embedded coin dispenser solution
for kiosks and self-service systems*

- Compact and integrated hopper-based design requires less space inside your self-service system
- Available in a wide variety of configurations to meet your requirements
- Controlled by a single intelligent 2-way interface
- Versatile and heavy-duty design for trouble-free operation
- Easy to load and empty



Coin Xpress: The coin dispenser of choice for kiosks and self-service systems

Telequip's CoinXpress is installed in kiosk and self-service systems around the world. Its configuration flexibility allows you to specify a system that matches your coin dispensing and coin management requirements. Its increased capacity requires less frequent fills and its quick and easy coin loading and unloading allows your customer to streamline their coin management processes.

Configuration Flexibility

Bin Configurations:

- Three-Bin (In-Line); Four-Bin (In-Line); Six-Bin (Face-to-Face)
- Custom discrete component solutions

Coin-Cup Options:

- Our cup - left side or right side
- Mate our coin exit to your chute and your cup

Coin Sets and Capacities – Denomination (Qty)

- US: 1c(1400), 5c(700), 10c(1880), 25c(600), \$1(450)
- UK: 1p(1008), 2p(450), 5p(1383), 10p(514), 20p(656), £1(313)
- Euro: 1c(2940), 2c(1072), 5c(933), 10c(966), 20c(480), 50c(395), €1(465), €1(382)
- Canada: 1c(1400), 5c(700), 10c(1880), 25c(600), \$1(450), \$2(380)
- Others available upon request

Advanced Electronics

- Single electronics board can control up to eight hoppers.
- Capable of monitoring the open/closed status of up to six external switch contacts. This can be used to monitor door switches and report the status via the interface.
- Capable of supplying 24VDC (max. 1A) up to three external devices. This can be used to control lights or lamps on the kiosk.
- Powered by a single 24VDC external switching power supply. Alternatively, you can power the unit yourself by providing 24VDC and 1.7 amps. max.

Advanced Firmware

- Even depletion and minimum dispense modes
- Firmware keeps a history of the coins dispensed by denomination and can report this to the host via the interface.
- Configurable alarm and sensor status can be indicated audibly and/or via comms.

Advanced Interface

- The CoinXpress is controlled via a simple ASCII-based interface over USB or RS-232.
- Drivers are available for OPOS and JPOS. Active X controls are also available.

Dimensions

- Three-Bin In-Line: 6.8"W x 10.4"D x 9.2"T
- Four-Bin In-Line: 6.8"W x 13.7"D x 10.2"T
- Six-Bin Face-to-Face: 13.6"W x 10.4"D x 9.2"T

Warranty

- 12-month depot warranty includes parts and labor
- Extended warranty available

Engineering Support

Telequip is happy to engage with your design staff and provide technical assistance as necessary.

For more information on how Telequip's CoinXpress can work with your kiosk, log onto www.telequip.com or contact a Telequip sales representative at **603-685-6999**.



Telequip[®]
Count On Us

Telequip Corporation
www.telequip.com

5 Industrial Way
Salem, NH 03079

Tel 1-603-685-6999
Fax 1-603-685-6998

© Copyright 2005 Telequip Corporation